



## ACRYLIC GLOSS WHITE

<b>Description:</b>	A highly durable 100% Acrylic exterior premium grade house paint, displaying excellent weathering properties and durability.		
<b>For Use On:</b>	Preprimed timber and weatherboards, concrete and masonry, primed metals and galvanised iron, fibrous plaster, wallboard, brickwork, fibre cement, concrete block.		
<b>Finish:</b>	Gloss		
<b>Abrasion Resistance:</b>	Very good		
<b>Dry Time:</b>	Touch Dry 30 minutes	}	Depending on temperature
	Recoat 2 hours	}	and humidity.
	Note: In cold damp conditions these times may be extended.		
<b>Usual number of coats:</b>	Two		
<b>Thinner/Clean Up:</b>	Water		
<b>Flash Point:</b>	Not applicable		
<b>Toxicity:</b>	Non toxic - lead and heavy metal free		
<b>Adhesion:</b>	Excellent		
<b>Solvent Resistance:</b>	Fair		
<b>Weathering Durability:</b>	Excellent, UV resistant		
<b>Colour:</b>	White, tintable to a range of fashion colours.		
<b>Application:</b>	Brush, roller or spray 10-15m <sup>2</sup> per litre		
<b>Container Sizes:</b>	1 Litre, 4 Litre, 10 Litre, 20 Litre.		
<b>Coverage:</b>	10-15m <sup>2</sup> per litre dependent upon surface texture.		
<b>Surface Preparation:</b>	Ensure surface to be painted is dry, free from dirt grease or other contamination, and dust free. Remove all loose flaky paint. Sand bare timber, putty nail holes and cracks after priming. Prime with Enviropaints Latex Pink or White Primer. Remove and treat efflorescence on masonry refer Data Sheet No 203.		
<b>Precautions:</b>	<p>a) Do not paint when surface temperature is below 10°C.</p> <p>b) In winter, do not start painting unless ambient temperature is above 13°C, and limit painting between 10.30am and 3pm. We recommend not painting in very damp or humid conditions.</p>		



-2-

### Acrylic Gloss White Continued.....

- c) Not suitable for opening sashes and doors; use Enviropaints Alkyd Gloss Enamel or Acro Water-Based Enamel.
- d) Do not use on chalky or powdery surfaces.
- e) Use on metals only if preprimed with Metal Primer beforehand.
- f) Stir well with a wide flat stirrer before use.
- g) Dampen porous masonry surfaces before coating especially in dry warm conditions.
- h) Protect from freezing during storage.

\* \* \* \* \*

**IN** the interest of personal safety Enviropaints Ltd recommend all paint products be stored securely away from children.

**ENVIROPAINTS** Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact Enviropaints free phone (0800) 80 PAINT (72468).

**THE** information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond Enviropaints Ltd control. Some guarantees may apply by law.