



SWIMMINGPOOL BLUE

- Description:** This is a non toxic hard wearing product.
- For Use On:** Formulated for swimming pools walls and floors that withstand the abuse of chlorinated water and general chemicals that are used in swimming pools in the treatment of water in swimming pools. A minimum of three coats is recommended. You need to make contact with your Enviropaints adviser Free phone 0800 80 PAINT before commencing as this product is a specialised product, correct advice is essential.
- Appearance:** Full Gloss.
- Durability:** Excellent.
- Heat Resistance:** Up to 120°C.
- Flammability:** This product is a Class 3 Dangerous Goods. Keep away from naked flames.
- Application:** Enviropaints Texture Broom, Brush or Roll.
- Coverage:** Approximately 9 square metres per one litre (100 square feet per one litre).
- Dry Time:** Approx. half an hour between coats. **Allow plenty of ventilation**
- Thinner:** Swimming Pool Thinners
- Clean Up:** Swimming Pool Thinners.
- Colour Range:** Blue, White and other colours on request
- Container Sizes:** 1 Litre, 4 Litre, 10 Litre, 20 Litre
- Surface Preparation:** As with any product, proper preparation is essential.
- a) Make sure all surfaces are **Clean and Dry – This is imperative.**
 - b) **Dirt and Grime:** Wash and scrub with water and wash again. Leave to dry.
 - c) **Oily substracts:** Remove with suitable solvent eg Swimming Pool Thinners.
 - d) If the surface is old and there is existing paint, we suggest that you water blast and in bad situations sand blasting could be necessary.
 - e) It is highly recommended before coating that a small testpot is used on existing paintwork to make sure that there is no adverse reaction.
 - f) Apply this product on a declining temperature between **5°C and 20°C**, this allows solvent to be sucked into the substrate. If applied in the heat of day small pin holing can form on surface as water vapour comes out of substrate.
 - g) Keep food stored away from area being painted as solvent fumes may taint. Adequate airflow is necessary when painting down in the pool.
- Coating Format:** It is best to brush in a **thinned first coat**, by **10% to 15%** to ensure a good key for your successive coats. A total of 3 coats is recommended.



Swimming Pool Blue Continued.....

IN the interest of personal safety Enviropaints Ltd recommend all paint products be stored securely away from children.
ENVIROPAINTS Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact Enviropaints free phone (0800) 80 PAINT (72468).
THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond Enviropaints Ltd control. Some guarantees may apply by law.