

OIL STAINS

- Description:** A semi transparent, general purpose oil stain based on linseed oil, providing good wood penetration and giving an enhanced appearance to the substrate. Very easy to apply.
- For Use On:** rough sawn timber weatherboards, fences, dressed timber, beams, plywood and wooden garden furniture.
- Colours:** Natural, Green, Ebonite, Redwood and Cedar
- Application:** Brush, Roll, Spray or Airless Spray. Very easy to apply. Saturate timber with ReidPaints Oil Stain.
- Dry Time:** 24 hours
- No of Coats:** 2-3 recommended
- Recoat Time:** 24 hours
- Coverage:** Depends upon surface texture - rough timber 3-5 m²/litre. Dressed timber 10-13 m²/litre
- Thinners:** Do not thin
- Clean Up:** Clean equipment using mineral turps.
- Durability:** Recoat after 2 summers (24 months).
In harsh climatic areas may require recoating in 12 months. Ensure joints and end grains are well coated.
- Surface Preparation:** **New Timber**
Ensure surface is dry, dust free and not contaminated (Remove contamination before coating)
- Natural not suitable on tanalised timber discolours timber to a black colour.**
- Old Exposed Timber**
Remove all contamination, moss or mould should be treated with a moss and mould solution as per manufacturers instructions. All stains or adhering coating should be sanded off.
- Limitations:** Should not be used over existing paints. Remove old paint back to bare timber before applying Oil Stain. Will not prevent cracking of plywood.
In very wet conditions will not prevent some water staining of end grain, if exposed.
- Contains volatile solvent, keep away from heat and open flame. Keep closed when not in use, avoid breathing vapour - ensure good air flow when applying in-doors. Stir very regularly during application to ensure consistency of colour.

* * * * *

Oil Stain continued.....

IN the interest of personal safety Reidpaints Ltd recommend all paint products be stored securely away from children.

REIDPAINTS Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact Reidpaints free phone (0800) 80 PAINT (72468).

THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond Reidpaints Ltd control. Some guarantees may apply by law.