

ACRYLIC VINYL LOW SHEEN WHITE

Description:	A superior quality vinyl acrylic copolymer low sheen paint exhibiting very good exterior and interior durability and washability.
Uses:	Normally used to give a low sheen appearance on interior walls and ceiling; suitably sealed Gibraltar board, soft board, particle board, sealed plaster, wallpaper. Not recommended for bathrooms, kitchens or laundries etc. Exterior use:- stucco, concrete blocks, fibre-cement, masonry. We do not recommend this product for weatherboards, doors or windows.
Finish:	Satin sheen.
Colour:	White and fashion colours.
Dry Time:	Touch dry 30 minutes } Depending on temperature Recoat in 2 hours } and humidity.
Usual number of coats:	One or two (depending on conditions)
Flash Point:	Not applicable.
Application Rate:	14m ² per litre depending on surface texture.
Toxicity:	Non-toxic - lead and heavy metal free (dry film)
Chemical Resistance:	Fair
Adhesion:	Excellent
Durability:	Very good, UV resistant.
Application:	Brush, roller or spray.
Solvent Resistant:	Fair
Primer Required:	Yes on interior timber. Use suitable sealer on composite board/gib-board etc.
Container Sizes:	1 Litre, 4 Litre, 10 Litre, 20 Litre.
Burnish Resistance:	Good, wipeable.
Thinner/Clean up:	Water

Acrylic Vinyl Low Sheen Continued.....

Surface Preparation: Ensure surface to be painted is dry, free from dirt grease or other contamination, and dust free. Remove all loose flaky paint. Fill and sand nail holes and imperfections. Sand bare timber, prime with ReidPaints Latex Timber Primer. Remove and treat efflorescence on masonry refer Data Sheet No. 203.

- Precautions:**
- a) Do not paint when surface temperature is below 10°C.
 - b) In winter, do not start painting unless ambient temperature is above 13°C, and limit painting between 10.30am and 3pm. We recommend not painting in very damp or humid conditions.
 - c) Not suitable for opening sashes and doors; use ReidPaints Alkyd Gloss Enamel or Acro Water-based Enamel.
 - d) Do not use on chalky or powdery surfaces
 - e) Stir well with a wide flat stirrer before use.
 - f) Dampen porous masonry surfaces before coating, & especially in dry warm conditions.
 - g) For optimum drying indoors ensure a free flow of air especially in humid weather.
 - h) Protect from freezing during storage.

* * * * *

IN the interest of personal safety Reidpaints Ltd recommend all paint products be stored securely away from children.

REIDPAINTS Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact Reidpaints free phone (0800) 80 PAINT (72468).

THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond Reidpaints Ltd control. Some guarantees may apply by law.