



ACRYLIC PRIMER SEALER UNDERCOAT OFF WHITE - INTERIOR/EXTERIOR

- Description:** Mixed Recycled copolymer Acrylics with added virgin vinyl copolymer and various pigments, producing an excellent primer sealer undercoat exhibiting very good exterior and interior sealing and undercoating characteristics.
- Uses:** Normally used as a primer sealer undercoat for successive topcoats, acrylic low sheen and gloss.
- Finish:** Flat
- Colour:** Off White
- Dry Time:** Touch dry 30 minutes } Depending on temperature
Recoat in 2 hours } and humidity.
- Usual number of coats:** One or two if necessary.
- Flash Point:** Not applicable.
- Application Rate:** 10-12m² per litre depending on surface texture.
- Toxicity:** Non-toxic - lead and heavy metal free (dry film)
- Adhesion:** Excellent
- Durability:** Very good.
- Application:** Brush or roller
- Container Sizes:** 4 Litre, 10 Litre.
- Thinner/Clean up:** Water
- Surface Preparation:** Ensure surface to be painted is dry, free from dirt grease or other contamination, and dust free. Remove all loose flaky paint. Fill and sand nail holes and imperfections. Sand bare timber, prime with Primer Sealer Undercoat Off White. Remove and treat efflorescence on masonry.
- Precautions:**
- a) Do not paint when surface temperature is below 10°C.
 - b) In winter, do not start painting unless ambient temperature is above 13°C, and limit painting between 10.30am and 3pm. We recommend not painting in very damp or humid conditions.
 - c) Do not use on chalky or powdery surfaces.
 - d) Stir well with a wide flat stirrer before use.



- e) Dampen porous masonry surfaces before coating, especially in dry warm conditions.
- f) For optimum drying indoors ensure a free flow of air especially in humid weather.
- g) Protect from freezing during storage.
- h) Follow instructions on the pail.

* * * * *

IN the interest of personal safety Enviropaints Ltd recommend all paint products be stored securely away from children.

ENVIROPAINTS Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact Enviropaints Ltd free phone (0800) 80 PAINT (72468)

THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond Enviropaints Ltd control. Some guarantees may apply by law.