



ENVIROPAINTS LTD P.O.BOX 152 OTAKI 5542 08008072468

PRODUCT TARSEAL ENHANCER	
Description	A bitumen based coating system designed to give an “as new” uniform finish to expanses of household and commercial driveways, courtyards and parking spaces.
Uses	Can be used across various substrates – patchy tarseal and concrete drives, carparks and carpads, forecourts and roadways.
Appearance	Low sheen when wet but dulls to flat finish on dry
Colour Range	Black
Durability	A hardwearing formulation designed for high traffic volume.
Coverage	4.5m ² per litre, this could vary lesser or greater according to the substrate roughness.
Surface Preparation	<ol style="list-style-type: none"> 1. Ensure the surface is clean and free from grease and dirt. 2. We recommend that surface are water blasted and allowed to dry. A good yard broom will work in most cases 3. Substrate should be a minimum of 10oC - do not paint on damp surfaces 4. Caution: Do not use any degreasing agents, waxes or detergents to clean surface before painting.
Application	Spray or brush and easily applied by DIY users giving a superb uniform finish. The product should be thoroughly stirred for at least 5 minutes before use. A high speed mixer is required for mixing. Recommended this product be broomed on especially the first coat
Dry Time	60 minutes at 20oC for highways and high traffic areas where quicker dry time is required, please contact our 0800 ENVIRO for advice
Thinner	Mineral Turpentine
Clean Up	Mineral Turpentine
Flammability in Can	Flammable - Class 3
Container Sizes	1 Litre, 4 Litre, 10 Litre & 20 Litre & 200 Litre
Coating Format	Recommend 1-2 coats. Recoat after 1 – 1 ½ hours
Risk Mitigation	No special protective clothing necessary but suggested protective clothing would be goggles, gloves and disposable overalls and in enclosed zones good ventilation required
Our Suggestions	Applied with a brush or broom is best. If you spray it carefully mask off all surrounds

In the interest of personal safety Enviropaints Ltd recommend all paint products be stored securely away from children. ENVIROPAINTS Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact Enviropaints free phone (0800) 80 PAINT (72468). THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond Enviropaints Ltd control. Some guarantees may apply by law.